



EVE8PD - POWER DISTRIBUTION HOUSING

- Power housing is specified per beam size (e.g. EVE8PD36 is for use in a 36" beam).
- 8 wire, 4 circuits (2+2 configuration).
- Accommodates two duplex receptacles per panel side.

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	L	D
	Power Distribution Housing	EVE8PD36	248	17 1/2	
		EVE8PD42	254	23 1/2	
		EVE8PD48	275	29 1/2	
		EVE8PD54	277	39 1/4	
		EVE8PD60	278	41 1/2	
		EVE8PD66	288	41 1/2	
		EVE8PD72	304	41 1/2	


EVE8CP - FLEXIBLE MESH JUMPER CABLE

- Used to connect two power distribution housings in a straight run, 90-degree or 120-degree connections.
- 18.5" flexible mesh jumper replaces EVE8CP20 jumper for corner post applications.

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	L	D
	Flexible Mesh Jumper Cable	EVE8CP17	135	17 1/2	
		EVE8CP18	167	18 1/2	

EVE8CPXX-H - PASS-THROUGH CABLE

- Flexible metal conduit with wire mesh distributes electrical power through non-powered beams.
- To calculate the length of a Pass-Through Cable, add the widths of the non-powered beam separating the powered panels (panels with distribution housing attached). To this, add 16" (distance from the edge of the panel to the distribution housing x 2).
- Add additional 3" when passing through a post. See the Tips at the beginning of the section for more details.
- Hybrid pass-through cables with wire mesh allows connection at 90 degree post at one end for Evolve panels including Beltline and Power Beam.

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	L	D
	Pass-Through Cable	EVE8CP40-H	226	40	
		EVE8CP46-H	234	46	
		EVE8CP52-H	240	52	
		EVE8CP58-H	255	58	
		EVE8CP64-H	266	64	
		EVE8CP70-H	274	70	
		EVE8CP76-H	277	76	
		EVE8CP82-H	288	82	
		EVE8CP88-H	298	88	
		EVE8CP94-H	305	88	
		EVE8CP100-H	315	100	
		EVE8CP106-H	330	106	
		EVE8CP118-H	346	118	
		EVE8CP130-H	380	130	
		EVE8CP142-H	397	142	
		EVE8CP154-H	416	154	
		EVE8CP172-H	447	172	
		EVE8CP190-H	468	190	
		EVE8CP208-H	486	208	

ELECTRICAL


EVE8CP50-H - JUMPER CABLE PANEL TO POWER BEAM

- Jumper cable to connect panel power distribution housing to power beam
 - Hybrid jumper cable with metal conduit and with 24" long wire mesh end to be able to plug into power beam
 - Panel to Power beam Post with vertical base feed covers to be ordered separately
- Power beam with electrical cut out must be ordered
 - 50" long Jumper cable will work with 24", 30" and 36" H Power beam

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	L	D
	Jumper cable Panel to Power Beam	EVE8CP50-H	229		50	


EVE8CI-1 - "I" CONNECTOR

- Female - Female connector used to connect two Pass-Through Cables
- Connects receptacles for 66" w and 72" w modules when two are required on one end

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	W	D
	"I" Connector	EVE8CI-1	101			

EVE8RD - DUPLEX RECEPTACLE TO CONVERT STANDARD 2 + 2 SYSTEM TO 3 + 1

- Duplex receptacle are rated for 15 Amps
 - EVE8RDA-4 = Duplex receptacle A without triangle to be utility circuit
 - EVE8RDB-4 = Duplex receptacle B without triangle to be utility circuit
- Up to 6 receptacles per circuit (24 per infeed) not to exude total 15 Amps per circuit
 - Standard in black. Available in White or Nevada with upcharge. Add \$3

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	L	D
	Duplex Receptacle	EVE8RDA-4	39	2	4 5/8	1 1/4
		EVE8RDB-4	39	2	4 5/8	1 1/4




EVE8RD - DUPLEX RECEPTACLE - 15 AMPS

- Duplex receptacles are rated for 15 Amps.
- EVE8RD1 = Circuit #1 (utility circuit)
- EVE8RD2 = Circuit #2 (utility circuit)
- EVE8RDA = Circuit A (dedicated)
- EVE8RDB = Circuit B (dedicated)

NOTE:

- EVE8RD1 and EVE8RD2 (#1 and #2 share common ground)
- EVE8RDA and EVE8RDB (A and B share common ground)
- Up to 6 receptacles per circuit (24 per infeed), not to exceed total of 15 Amps per circuit.
- Standard in black. Available in White or Nevada with upcharge.


DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D
 Duplex Receptacle	EVE8RD1	39	2	4 5/8	1 1/4
	EVE8RD2	39	2	4 5/8	1 1/4
	EVE8RDA	39	2	4 5/8	1 1/4
	EVE8RDB	39	2	4 5/8	1 1/4
	EVE8RD1SND	44	2	4 5/8	1 1/4
	EVE8RD2SND	44	2	4 5/8	1 1/4
	EVE8RDASND	44	2	4 5/8	1 1/4
	EVE8RDBSND	44	2	4 5/8	1 1/4
	EVE8RD1WHT	44	2	4 5/8	1 1/4
	EVE8RD2WHT	44	2	4 5/8	1 1/4
	EVE8RDWHT	44	2	4 5/8	1 1/4
	EVE8RDBWHT	44	2	4 5/8	1 1/4

EVE8RDxca - CONTROLLED DUPLEX RECEPTACLE

- Meets California Title 24, Federal and LEED certification guidelines
- Allows circuit to be controlled or switched off when utility is not in use.
- Duplex receptacles are rated for 15 Amps.
- EVE8RD1CA = Circuit #1 (utility circuit)
- EVE8RD2CA = Circuit #2 (utility circuit)
- EVE8RDACA = Circuit A (dedicated)
- EVE8RDBCA = Circuit B (dedicated)

NOTE:


- EVE8RD1CA and EVE8RD2CA (#1 and #2 share common ground)
- EVE8RDACA and EVE8RDBCA (A and B share common ground)
- Up to 6 receptacles per circuit (24 per infeed), not to exceed total of 15 Amps per circuit.
- Available in BLK finish only.

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D
 Duplex Receptacle	EVE8RD1CA	42	2	4 5/8	1 1/4
	EVE8RD2CA	42	2	4 5/8	1 1/4
	EVE8RDACA	42	2	4 5/8	1 1/4
	EVE8RDBCA	42	2	4 5/8	1 1/4

ELECTRICAL


EVEUSB01 - USB MODULE

- Includes two USB ports.
- Available in White and Black.

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	L	D
	USB Module - White	EVEUSB01WHT	242	2	4 5/8	1 1/4
	USB Module - Black	EVEUSB01BLK	242	2	4 5/8	1 1/4


EVE8FR3PB - POWER ENTRY FOR POWER BEAM

- Snaps in to power distribution housing
- Includes 84" long flexible vinyl conduit
- Includes bracket to attach within vertical infeed cover
- Must be hardwired to source by licensed electrician

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	W	D
		EVE8FR3PB	518		84	

EVE8FR3PBD - DOUBLE POWER ENTRY FOR POWER BEAM


- Each power feed entry snaps into separate power distribution housing
- Includes two 84" long flexible vinyl conduit
- Includes double bracket to attach to Vertical base power feed cover leg
- Must be installed in middle between two power beams, one base feed plugs to power beam on opposite side of leg than attached bracket
- Vertical base power feed cover with leg to be ordered separately
- Must be hardwired to source by licensed electrician

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	W	D
		EVE8FR3PBD	865		84	

NOTE: Always determine that each individual harness is electrically connected to only one power supply.

EVE8EC - CEILING POWER ENTRY


- Must specify at a 90 or 120 Degree Post
- Post extension specified separate
- Floor plate must be separate on post with ceiling infeed

	DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
				H	L	D
	Ceiling Power Entry	EVE8EC1	304		132	
		EVE8EC2	532		144	
		EVE8EC3	600		180	

EVEENY-2PB - HARDWARE POWER ENTRY BOX - NEW YORK FOR POWER BEAM

- A licensed electrician must provide hard wire connection within the junction box.
 - Box attaches vertically with screws to leg between Vertical base feed covers
 - Vertical base power feed cover with leg to be ordered separately
- Must be installed in middle between two power beams, plugs to power beam on opposite side of leg than attached box
 - For use with Power Beam only

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D




Hardware Power Entry Box - New York	EVEENY2PB	503	3	28	2 1/5
-------------------------------------	-----------	-----	---	----	-------

EVEJBC-1PB - HARDWARE JUNCTION BOX - CHICAGO FOR POWER BEAM

- Can be retrofitted in any size of power beam at the receptacle location.
 - Gives access from one side only at each location.
 - Customer to supply conduit, wiring, receptacle, and face plate.
- A licensed electrician must provide hardware connection with the junction box.
 - 2 per power beam
 - For use with Power Beam only

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D




Hardware Junction Box - Chicago	EVEJBC-1PB	116			
---------------------------------	------------	-----	--	--	--

EVDPE - POST EXTENSION DATA/ COMM LAY-IN

- Attaches to the top of post to bring power and/or data cables from ceiling to panel power way
 - Three-sided power pole with snap-on fourth side
 - Post extension can be open on one side for lay-in or power and/or data cables
 - Made of aluminum and can be field cut
- Accommodates up to 25 CAT 5 cables with electric. Accommodates up to 45 CAT 5 cables without electric
 - Ceiling infeed installed on one way post with T Leg requires securing post with two Floor mount plates
 - Post extension bigger then 82"H is made from two parts

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D



Post Extension Data/Comm Lay-in	EVDPE64	195	64	2	
	EVDPE82	236	84	2	
	EVDPE88	350	88	2	
	EVDPE94	375	94	2	
	EVDPE100	399	100	2	

EVAFMB01 - FLOOR MOUNT PLATE

- Attaches to floor.
 - Secures beam to floor.
 - Attachement screws are not included.
- Care should be taken to use correct fastners for type of floor.
 - Available in chrome finish only.


DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D
Floor Mount Plate	EVAFMB01	98	0.25	5	2.5



EVPBECH34 - E-CHAIN WITH BRACKET

- E-Chain provides cable management from the Power Beam to a height adjustable table
 - Includes bracket to attach to bottom of Power Beam
- E-chain provides wire management for all height adjustable table heights
 - Available in black only

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D
E-Chain with Bracket	EVPBECH34	448	41	1	2



EVPBT01 - POWER BEAM TRAY

- Power beam tray provides support for wires
 - Can be used with power beam only
- Available in standard and premium paint finishes

DESCRIPTION	PRODUCT CODE	LIST PRICE	DIMENSIONS/INCHES		
			H	W	D
Power Beam Tray	EVPBT01	48	12	1.25	3.5

